

UP TO **20** LOADED RAILCARS

TRACTIVE EFFORT: 30,000 LBS (133KN) SINGLE COUPLED WITHOUT WEIGHT TRANSFER TO LOADED OR EMPTY RAILCAR

**STANDARD FEATURES**

- 90 gallon fuel tank
- ABS vehicle brakes
- Air knife
- Anti-slip traction control
- CAN-bus electrical system
- Door mounted windshield wipers
- Engine diagnostic adapter: console
- Exterior mounted cameras with color

The Commander Series Shuttlewagons shares many of the same features as the larger Navigator but comes in a smaller package. It is designed to complete up to 35,000 lbs of tractive effort from one coupler. Compact yet powerful Commander Series pulls as much weight as other manufacturers' larger models.

**SWX420 GENERAL SPECIFICATIONS**

FUEL CAPACITY	90 gallons (340.69 ltr)
HYDRAULIC RESERVOIR CAPACITY	50 gallons (189.27 ltr)
AIR TANK CAPACITY (RAIL BRAKES)	30 gallons (113.56 ltr)
AIR TANK CAPACITY (VEHICLE BRAKES)	5 gallons (39.74 ltr)
AIR FILTER	Dry replacement element
OIL & FUEL FILTERS	Replacement element
WHEEL BASE	92" (2337 mm)
WIDTH	120" (3048 mm)
HEIGHT	130.5" (3327 mm)
LENGTH	242" (6147 mm)
GROUND CLEARANCE	10½"(266.7 mm)
WEIGHT	46,000 lbs (20,870 kg)
FIRST GEAR	0 to 3mph/4.8kmh
SECOND GEAR	0 to 7mph/11.2kmh
THIRD GEAR	0 to 12mph/27.3km/h



180-degree rotating console with a multifunction display. Dual four-way air suspension seats for operation from either side of cab when in rail mode.



Wide range AAR sliding couplers are air released and hydraulically positioned to improve pulling performance on curves and grades.



Pull out sander boxes with wide mouth lids for easy loading. Air activated sanders for smooth dispensing.



Powerful air knife increases capacities up to 50% in adverse weather.



